

AEI COMMUNICATIONS CORP.

1001 Broadway, Millbrae, California 94030 Direct: (415) 706-2907 ,Tel: (650) 552-9416

AGR-6106S Analog Phone

Model: AGR-6106S

Esthetic Design 2013/02



Features & specification

Keys

- Dial Keys (0~9, *, #)
- Function Keys
 - Hard Keys Standard phone function supported features, such as Speaker, Volume up/down and speed dial keys x 6

Phone

- Single line telephone system with speakerphone
- Adjustable High-low ringer (2 way selectable switch)
- 8 steps speakerphone digital volume control
- 4 steps handset digital volume control
- 6 non volatile one-touch programmable speed dial memory button
- Tone dialing only
- Hearing Aid Receiver Compliant
- PBX / Standard Line compatible
- Multi Purpose LED indicator for Message Waiting and Incoming Ring



AEI COMMUNICATIONS CORP.

1001 Broadway, Millbrae, California 94030 Direct: (415) 706-2907 ,Tel: (650) 552-9416

AGR-6106S Analog Phone

Model: AGR-6106S

Power

Line Power (without AC adaptor or battery)

Jack

RJ11 Jack x 1

Size and Weight

Dimensions: 191mm(L) x 110mm(W) x 106mm(H), Weight: 576g

Regulatory		USA	EU	
ЕМІ	FCC Part 15B			
EMC	EN55022 & EN55024			
PSTN	Part 68			
RoHS	Comply with Directive 2002/95/EC RoHS (as amended by Commission Decision 2005/613/EC)			
Temperature	Storage:	Cold point at -10°C. Hot point at +60°C. Damp point at 80% RI	H, Temp at +60°C.	
	Operating:	Cold point at 0°C. Hot point at +45°C. Damp point at 80% RI	⊣, Temp at +45°C.	