



AEI COMMUNICATIONS CORP.

1001 Broadway, Millbrae, California 94030

Direct: (415) 706-2907 ,Tel: (650) 552-9416

Analog Phone for Desktop/Bedside

Model: ASP-6210-S/ASP-6110-S

1. Esthetic Design

2015/01 v0.1

ASP-6210-S



ASP-6110-S





AEI COMMUNICATIONS CORP.

1001 Broadway, Millbrae, California 94030

Direct: (415) 706-2907 ,Tel: (650) 552-9416

Analog Phone for Desktop/Bedside

Model: ASP-6210-S/ASP-6110-S

2. Features / Software Specifications

	ASP-6210-S	ASP-6110-S
Keys	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2 with red color LED Function keys Conference, Hold, Redial, Mute, Speaker, Message, Volume up/down, 10 speed dial keys 	<ul style="list-style-type: none"> (0~9, *, #) N/A Flash, Redial, Mute, Speaker, Message, Volume up/down, 10 speed dial keys
Phone Features	<ul style="list-style-type: none"> One or Two Lines 3-Way Conference(ASP-6210-S only) Call Hold and resume(ASP-6210-S only) Mute and Resume Red color message waiting indicator for ringing and message waiting 	<ul style="list-style-type: none"> 10 programmable speed dials Selectable flash timing(ASP-6110-S only) Handset, Speaker volume control Ringer volume switch Redial last call

3. Hardware Specifications

	ASP-6210-S	ASP-6110-S
Jacks	RJ14 PSTN jack x 1 RJ11 PSTN jack x 1 RJ9 Handset jack x 1	RJ11 PSTN jack x 2 RJ9 Handset jack x 1
LED Indications	<ul style="list-style-type: none"> Line keys, Conference, Mute, Speaker keys, and Message waiting indicator 	
Power	<ul style="list-style-type: none"> Telephone line powered 	
Ring Voltage	<ul style="list-style-type: none"> 40V RMS minimum 	
Line cord	<ul style="list-style-type: none"> 10 feet x 1 	
Size and Weight	<ul style="list-style-type: none"> Dimensions:227mm(L) x158mm(W) x 141mm(H), Weight: 835g 	

4. Regulatory

	USA	EU
PSTN	FCC TIA-968B & Part 68	TBR21
EMC	FCC Part 15B	EN55022 & EN55024
RoHS	<ul style="list-style-type: none"> Comply with Directive 2002/95/EC RoHS (as amended by Commission Decision 2005/613/EC) 	
Temperature	<ul style="list-style-type: none"> Storage: Low Temperature at -10°C. High Temperature at +60°C Operating: Low Temperature at 0°C. High Temperature at +40°C. 	