



# AEI COMMUNICATIONS CORP.

1001 Broadway, Millbrae, California 94030

Direct: (415) 706-2907 ,Tel: (650) 552-9416

## SIP Phone for Desktop/Bedside

Model: SSP-2210-S/SSP-2110-S

### 1. Esthetic Design

2015/01 v0.1

**SSP-2210-S**



**SSP-2110-S**





# AEI COMMUNICATIONS CORP.

1001 Broadway, Millbrae, California 94030

Direct: (415) 706-2907 ,Tel: (650) 552-9416

## SIP Phone for Desktop/Bedside

Model: SSP-2210-S/SSP-2110-S

### 2. Features / Software Specifications

Keys	SSP-2210-S	SSP-2110-S
	<ul style="list-style-type: none"> <li>Dial keys (0~9, *, #)</li> <li>Line keys Line1, Line2 with red/green color LED</li> <li>Function keys Conference, Hold, Redial, Mute, Speaker, Message, Volume up/down, 10 speed dial keys</li> </ul>	<ul style="list-style-type: none"> <li>(0~9, *, #)</li> <li>N/A</li> <li>Hold, Redial, Mute, Speaker, Message, Volume up/down, 10 speed dial keys</li> </ul>
Phone Features	<ul style="list-style-type: none"> <li>One or Two Lines</li> <li>Message key with message waiting indicator</li> <li>3-Way Conference(SSP-2210-S only)</li> <li>Call Hold and resume</li> <li>Mute and Resume</li> </ul>	<ul style="list-style-type: none"> <li>10 programmable speed dials</li> <li>Handset, Speaker and ringer volume control</li> <li>Redial last call</li> <li>Red color message waiting indicator for ringing and message waiting</li> </ul>
Display Contents	<ul style="list-style-type: none"> <li>Talking time</li> <li>IP Address</li> <li>MAC Address</li> </ul>	<ul style="list-style-type: none"> <li>SIP Register Status</li> <li>Firmware Version</li> <li>Failed Network link Warning</li> </ul>
Easy Administration	<ul style="list-style-type: none"> <li>Web GUI</li> <li>Auto provisioning via TFTP</li> <li>Firmware upgrade via TFTP</li> </ul>	
Codec	<ul style="list-style-type: none"> <li>G.711</li> </ul>	
Network Protocol	<ul style="list-style-type: none"> <li>HTTP/DHCP server</li> <li>Static / DHCP IP assignment</li> <li>ToS / VLAN IEEE 802.1 p/q</li> </ul>	
SIP	<ul style="list-style-type: none"> <li>SIP V2 (RFC3261)</li> </ul>	
Security	<ul style="list-style-type: none"> <li>Web login authentication for web setup</li> <li>MD5 for SIP authentication (RFC 2069/ RDC2617)</li> </ul>	
DTMF	<ul style="list-style-type: none"> <li>In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)</li> </ul>	
Voice Quality	<ul style="list-style-type: none"> <li>CNG: Comfortable noise generator</li> <li>Echo canceller: LEC / AEC</li> <li>Jitter buffer/PLC</li> </ul>	
Tones	<ul style="list-style-type: none"> <li>Ring back tone (local), Busy tone, Dial tone</li> </ul>	

### 3. Hardware Specifications

Display	<ul style="list-style-type: none"> <li>16 x 2 dot matrix LCM with white backlight</li> </ul>
LED Indications	<ul style="list-style-type: none"> <li>Line keys, Conf/Hold, Mute, Speaker keys, and Message waiting indicator</li> </ul>
Power	<ul style="list-style-type: none"> <li>PoE module: IEEE 802.3af</li> <li>AC adaptor: Input: 100 ~ 240 VAC, Output: 6V / 1A (optional)</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>RJ45 10/100 Mbs; LAN port x 1, PC port x 1, DC jack x 1, RJ9 Handset jack x 1</li> </ul>
Ethernet cable	<ul style="list-style-type: none"> <li>9 feet x 1</li> </ul>
Size and Weight	<ul style="list-style-type: none"> <li>Dimensions:227mm(L) x158mm(W) x 141mm(H), Weight: 905g</li> </ul>

### 4. Regulatory

	USA	EU
EMI	FCC Part 15B	EN55022
Safety		EN 60950-1
EMC		EN 55024 IEC 61000-4-4

