

VS-6104-S(A)

Single Line Analog
Speaker Phone



- Single line analog phone.
- Wall mountable speaker phone.
- Customizable service dials.
- Message key with indicator.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

| | |
|----------------|--|
| Keys | <ul style="list-style-type: none"> • Dial keys (0~9, *, #) • Line keys N/A • Function keys Speaker, Mute, Volume UP/Down, 4 service dial keys |
| Phone Features | <ul style="list-style-type: none"> • Single line telephone system with speakerphone • Tone dialing only • PBX / Standard Line compatible • Mute and Resume • Ringer volume switch |

2. Hardware Specifications

| | |
|-----------------|---|
| LED Indications | <ul style="list-style-type: none"> • MUTE(red), SPEAKER(red), MESSAGE(red) keys |
| Power | <ul style="list-style-type: none"> • Line Power (without AC adaptor or battery) |
| Ring Voltage | <ul style="list-style-type: none"> • 40V RMS minimum |
| Line cord | <ul style="list-style-type: none"> • 0.7 feet x 1 |
| Jacks | <ul style="list-style-type: none"> • RJ11 PSTN jack x 1 |
| Size and Weight | <ul style="list-style-type: none"> • Dimensions: 180mm(L) x 100mm(W) x 27.5 mm(H), Weight: TBD |

3. Regulatory

| | USA | EU |
|-------------|---|--|
| PSTN | Part 68 | TBR 21 |
| EMI | FCC Part 15B | EN55032 & EN55024 |
| RoHS | <ul style="list-style-type: none"> • Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) | |
| Temperature | <ul style="list-style-type: none"> • Storage: Low temperature at -10°C • Operating Low temperature at 0°C | <ul style="list-style-type: none"> High temperature at +60°C High temperature at +40°C |

Model:
VS-6104-S(A)

